



BILL



LINEAR TELESCOPIC OPERATOR

personalised release key

up to 4.0 m



CONTROL UNITS:

- BILL30M** — BRAINY HEADY
- BILL40M** — BRAINY HEADY
- BILL4024** — BRAINY24^{PLUS}
BRAINY24
TRUST24
- BILL50M** — BRAINY HEADY



230 Vac



- Irreversible 230 Vac electromechanical geared motor

24 Vdc | intensive use

- 24 Vdc irreversible electromechanical geared motor for intensive use
- Anti-crushing system with amperometric sensor
- Prepared for battery back-up system

Irreversible electromechanical geared motor, available with power options 230 VAC or 24 VDC. Ideal for automation devices for wrought iron gates, this product is very small and suitable for a quick and easy installation. Worm screw protected by a scraper ring and stainless steel stem, suitable for dusty or sandy environments, or places with aggressive weather conditions. Available in right or left side versions.

www.beninca.com



	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
BILL30	909	875	300	100-150	100-150	60-100
BILL40	1109	1075	400	100-200	100-200	65-150
BILL50	1309	1275	500	120-250	120-250	80-190

COMPLETE KITS



MOTORS



CONTROL UNIT



PHOTOCELLS




FLASHING LIGHT



TRANSMITTER

KBILL30M	2x BILL30M	1x HEADY	1x PUPILLA.T	1x LAMPY	1x TO.GO2VA
KBILL40M	2x BILL40M	1x HEADY	1x PUPILLA.T	1x LAMPY	1x TO.GO2VA
KBILL4024	2x BILL4024	1x TRUST24	1x PUPILLA.T	1x LAMPY	1x TO.GO2VA


BENINCA




B.SR
Multiposition brackets for one operator.




BILL30.CO
Telescopic stem cover accessory.



BILL40.CO
Telescopic stem cover accessory.




BILL50.CO
Telescopic stem cover accessory.




SNC.90
Bracket for 90° cable orientation.
Package of 2 pcs.



DU.V96
12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.



DU.V90
12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.



DU.9990
Covering plate for DU.V90.



E.LOCK
230 Vac vertical electric lock, supplied with counterplate.




E.LOCKSE
Extended cylinder for E.LOCK electric lock. It allows unlocking gates up to 55mm-thick from the outside.




XLB.CB
Battery box fitted with universal bracket and cables. IP54.



DA.LB
Galvanized column for outdoor installation of LB box.



BRAINY24.CB-SW
Accessory equipped with 1.2 Ah batteries and support bracket.



BRAINY24.CB
Accessory with CBY.24V battery charger, 1.2 Ah batteries and support bracket.

AUTOMATISMI BENINCÀ SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

TECHNICAL DATA	BILL30M*	BILL40M*	BILL50M*	BILL4024*
Motor supply	230 Vac (50-60Hz)	230 Vac (50-60Hz)	230 Vac (50-60Hz)	24 Vdc
Max absorbed current	1.1 A	1.1 A	1.1 A	5 A
Max Thrust	2800 N	2800 N	2800 N	2000 N
Opening time	16"	18"	21"	15"
Duty cycle	30%	30%	30%	intensive use
Standard stroke	300 mm	400 mm	500 mm	400 mm
Max stroke	320 mm	420 mm	520 mm	420 mm
Protection level	IP54	IP54	IP54	IP54
Operating temperature	-20°C /+50°C	-20°C /+50°C	-20°C /+50°C	-20°C /+50°C
Leaf max dimension	2.5 m	3.5 m	4.0 m	3.5 m
Weight	6.1 kg	6.7 kg	6.9 kg	5.5 kg
Items no. per pallet	62	48	48	48
Kit weight	14.6 kg	15.5 kg	16.2 kg	14.6 kg
Kits no. per pallet	40	30	30	30